

# ZT34J

## TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

### Highlights

- Perform dual capacity design, up to 300/454kg
- Rough terrain chassis features swing axle function, easy to achieve 45% gradeability
- Innovative outrigger design; great reliability, smooth telescopic system and tire wear prevention (option)
- Smooth boom extension 30% more efficient compared to double-cylinder system
- Best in class work platform, 10 % larger than similar models

### Features

#### Standard

- Horn
- All motion alarm
- Proportional control
- Self-closing entry gate
- Flashing amber beacon
- Auto-leveling system
- Emergency stop button
- Over tilt protection system
- Emergency descent system
- On-board diagnostic system
- Oscillating axle
- 4.3' LED display
- Load sensing system
- Swing-out engine tray
- Secondary Guarding System





# ZT34J

## TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

## Technical data

<b>Model</b>	ZT34J
<b>Size</b>	
Work Height	36m
Platform Height	34m
Horizontal Outreach	24.2m
A - Stowed Length	13.50m
B - Stowed Width	2.49m
C - Stowed Height	3m
D - Platform Length	2.44m
E - Platform Width	0.91m
F - Wheelbase	3.81m
Tread	2.49/3.87m
G - Ground Clearance	0.41m
<b>Performance</b>	
"Platform capacity (Unrestricted / Restricted)"	300/454kg
Drive Speed (Working)	5km/h
Gradeability	45%(24°)
Turning Radius (Inside)	3.3/7.7m
Turning Radius (Outside)	8.2/10.8m
Turret Swing	360° continuous
Platform Rotation	±90°
Tail Swing	1.20m
Jib (Range of Articulation)	130° (-55° ~ 75°)
Max. Wind Speed	12.5m/s
<b>Power</b>	
Engine	Cummins QSF 2.8 54kW/2400rpm
Fuel Tank Capacity	200L
Control Voltage	12V DC
Hydraulic System Capacity	250L
Drive Mode	4WD
Steering Mode	Four wheels/Front wheel/Crab
<b>Tire</b>	
Type	IN445/50D710 Foam-filled Tires
<b>Weight</b>	
Gross	19300kg

