

ZT58J

TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

Highlights

- Work height up to 58.8m and horizontal outreach up to 25.5m
- First polygonal boom on the market, 10% lighter than conventional design
- New improved version with vertical stiffness increased by 25% and torsion resistance augmented by 20%

Features

Standard

- Horn
- Proportional control
- All motion alarm
- Flashing beacon
- Self-closing entry gate
- Emergency descent system
- Emergency stop button
- Auto-leveling system
- On-board diagnostic system
- Tilt protection system
- Load sensing system
- 4.3" Led display
- Swing-out engine tray
- Anemograph





ZT58J

TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

Technical data

Model	ZT58J
Size	
Work Height	58.8 m
Platform Height	56.8 m
Horizontal Outreach	25.5 m
A - Stowed Length	14.4 m
B - Stowed Width	2.5 m
C - Stowed Height	3.06 m
D - Platform Length	2.44 m
E - Platform Width	0.91 m
F - Wheelbase	5.357m / 4.69m
Tread	2.50m / 5.15m
G - Ground Clearance	0.4 m
Performance	
Platform capacity (Unrestricted / Restricted)	300kg / 454kg
Drive Speed (Working)	4.5 km/ h
Gradeability	45% (24°)
Turning Radius (Inside)	6.79m / 2.57m
Turning Radius (Outside)	8.43m / 6.39m
Turret Swing	360° non-continuous
Platform Rotation	±90°
Tail Swing	2.25 m
Jib (Range of Articulation)	125° (-55° ~ 70°)
Max. Wind Speed	12.5 m/s
Power	
Engine	Cummins QSF3.8
Fuel Tank Capacity	200 l
Control Voltage	12V DC
Hydraulic System Capacity	400 l
Drive Mode	4WD
Steering Mode	Four wheels / Front wheel / Crab
Tire	
Type	445/50 D710 Foam-filled tires
Weight	
Gross	29600 kg

